Serial No. 10/600,096 Docket No. 146712010300

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

09-149614

(43)Date of publication of application: 06.06,1997

(51)Int.CI.

HO2K 21/22 G11B 19/20

(21)Application number : 07-300907

(71)Applicant: MATSUSHITA ELECTRIC IND CO LTD

(22)Date of filing:

20.11.1995

(72)Inventor: TOYOSHIMA HIROYOSHI

(54) SPINDLE MOTOR

(57)Abstract:

PROBLEM TO BE SOLVED: To reduce the unbalance value and improve the efficiency of the assembly work when a magnetic disc is clamped. SOLUTION: A motor has a housing 1, a rotor hub part 2 which can rotate freely relatively to the housing 1 and to which a magnetic disc 9 is attached, a shaft 4 which is mated with a sleeve part 3 fixed to the housing 1 and a sleeve part 3 fixed to the rotor hub part 2 so as to rotate freely, a magnet 6 attached to the rotor hub part 2 and a stator core 7 which is so fixed to the housing 1 as to face the magnet 6. The shaft 4 is so supported as to rotate freely by the sleeve parts 3 with fluid material therebetween. A screw hole 13 for a clamping screw 12 by which a clamping member 11 which clamps the isl magnetic disc 9 is fixed is provided in the end surface of the shaft 4.



